



KIMTECH PURE* M3 Pleat-Style Face Masks

Codes: 62465, 62466

Product Information

Cod	de	Description	Color	Style	Size	Case Count
624	65	M3 Face Mask with Knitted Earloops	White	Pleated	7"	50/bag, 500/case
624	66	M3 Face Mask with Soft Ties	White	Pleated	7"	50/bag, 500/case

Physical Properties	Results	Test Method
Particle Filtration Efficiency @ 0.1 micron	99.5%	ASTM F1215-89
Differential Pressure in mm H ₂ O @ 8 LPM flow rate	1.33	MIL-M-36954C
Bacterial Filtration Efficiency @ 3.0 micron	98.7%	MIL-M-36954C



Mask Construction					
Binding / Ties	White, Spunlaced Polyester				
Nosepiece	Fully enclosed, soft, malleable aluminum				
Outer Facing	Clear, Polyethylene, Apertured Film				
Inner Facing	White BiCoSof™ Fabric¹				
Filter Media	White, High Efficiency, Meltblown Polypropylene				
Earloops	White, Tubular Knitted Polyester/Polyurethane				
Construction	Ultra Sonic Bonding				

¹BiCoSof Fabric is a Spunbond Material made from a bicomponent polypropylene/polyethylene (PP/PE) fiber.

Additional Information:

- Manufactured in ISO 9001:2000 registered facilities.
- All Face Masks are double bagged.
- Recommended for Class 3 or higher cleanroom environments.
- Certificates of Conformance are available on request, send email to kcpcerts@kcc.com.

Workmanship Requirements

Face Mask shall be made in accordance with reasonable industry practice with respect to holes, tears, wrinkles, cleanliness, odors and foreign materials or dirt.

For additional information: 1-888-346-4652 or kimtech@kcc.com



